


**10K SWING CHECK VALVE** Pressure-Temperature Rating: 1.0MPa: 180 C




| Parts             | UOB                 | UOBM          |
|-------------------|---------------------|---------------|
| Body              | SCS13A              | SCS14A        |
| Cap               | SCS13A/SUS304       | SCS14A/SUS316 |
| Disc              | SCS13A              | SCS14A        |
| Hinge pin         | SUS304              | SUS316        |
| Plug              | SUS304              | SUS316        |
| Gasket (for plug) | Asbestos-free sheet |               |

Face-to-Face Dimensions: JIS B2011 \*Except flange thickness.  
 End Flange Dimensions: JIS B2220\*  
 Wall Thickness: KITZ Std.

UOB UOBM

| Nominal Size | Unit:mm |     |     |       |       |     |       |     |
|--------------|---------|-----|-----|-------|-------|-----|-------|-----|
|              | 1/2     | 3/4 | 1   | 1 1/4 | 1 1/2 | 2   | 2 1/2 | 3   |
| L            | 85      | 95  | 110 | 130   | 150   | 180 | 210   | 240 |
| H            | 45      | 55  | 61  | 71    | 72    | 81  | 95    | 105 |

**TYPE 200 SWING CHECK VALVE** Pressure-Temperature Rating: 1.0MPa: 180 C  
200psi. W.O.G.: 350 F S.P.




| Parts             | AKUOM        |
|-------------------|--------------|
| Body              | CF8M         |
| Cap               | CF8M/316     |
| Disc              | CF8M         |
| Hinge pin         | 316          |
| Plug              | 316          |
| Gasket (for plug) | Aramid fiber |

Face-to-Face Dimensions: KITZ Std.  
 End Thread Dimensions: ASME B1.20.1  
 Wall Thickness: KITZ Std.

AKUOM

| Nominal Size | Unit:mm |     |    |       |       |     |       |     |
|--------------|---------|-----|----|-------|-------|-----|-------|-----|
|              | 1/2     | 3/4 | 1  | 1 1/4 | 1 1/2 | 2   | 2 1/2 | 3   |
| L            | 65      | 80  | 90 | 105   | 120   | 140 | 180   | 200 |
| H            | 45      | 55  | 61 | 71    | 72    | 81  | 93    | 104 |

**10K LIFT CHECK VALVE** Pressure-Temperature Rating: 1.0MPa: 180 C



| Parts | UN            |
|-------|---------------|
| Body  | SCS13A        |
| Cap   | SCS13A/SUS304 |
| Disc  | SUS304        |

Face-to-Face Dimensions: JIS B2011  
 End Thread Dimensions: JIS B0203  
 Wall Thickness: KITZ Std.

UN

| Nominal Size | Unit:mm |     |     |    |       |       |     |
|--------------|---------|-----|-----|----|-------|-------|-----|
|              | 3/8     | 1/2 | 3/4 | 1  | 1 1/4 | 1 1/2 | 2   |
| L            | 55      | 65  | 80  | 90 | 105   | 120   | 140 |
| H            | 50      | 53  | 54  | 62 | 66    | 76    | 85  |