



EP

AP

ES

CP

EP

AP

ES

CP

Mod. 596

Mod. 696

Connection: Flange x Flange
 DN1 x DN2: 25x32 to 400x500
 Material: Carbon steel
 PN-25/40/63/100/160. PMS-62 bar
 Stainless steel
 PN-25/40/63/100/160. PMS-62 bar
 Seal: Metal

Connection: Flange x Flange
 DN1 x DN2: 25x40 to 300x400
 Material: Carbon steel
 PN-25/40/63/100/160. PMS-95 bar
 Stainless steel
 PN-25/40/63/100/160. PMS-95 bar
 Seal: Metal

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open instantly and totally.
 Design in accordance with "International Standard ISO 4126-1 Safety Valves".

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open instantly and totally.
 Design in accordance with "International Standard ISO 4126-1 Safety Valves".

Depending on version



-60°C to +450°C



0,20 bar to 62,00 bar



Steam/Gases/Liquids

Depending on version



-60°C to +450°C



0,20 bar to 95,00 bar



Steam/Gases/Liquids